Central Control

Model: Heatmiser TouchPad

Headline Information

Central Control
Part Ref: Heatmiser TouchPad

Up to 32 rooms can be controlled from the full colour TFT Display meaning that walking around each room to turn up or down the heating is a thing of the past.

The TouchPad is also fully compatible with the Heatmiser NetMonitor system, our remote access system.

Display
TouchScreen 4.3" TFT
Colour LCD

Number Of Zones
32 (Max)

Titles
Give each room a title

Passcode Protect
When enabled, the user must enter a passcode in order to access the system.

Key Features

Home and Away
This feature gives you a simple way of turning off your heating system whilst you are away. On your return, pressing the Home button will re-enable the system. Ideal when you have a holiday home and are not sure when you will return.

Profiles
Gives the ability to store a set of comfort levels for a group of rooms. This setting can be applied as and when required, for example at the start of a new shift.

Holiday
Use the holiday feature to put the heating into frost mode whilst you are away. At the end of the holiday, each room will revert back to the programmed time, ensuring your home is warm on your return.

Temperature Hold
Use this function to hold a desired temperature for a fixed period, ideal for unexpected activities. Apply to a single or multiple rooms.

Hot Water Boost
Use the hot water boost to quickly override the hot water settings.

Auto GMT Correction
Automatically adjusts the clocks in all of the thermostats at the start of summer and winter time.

Auto Time Sync
Syncronises all of the thermostat clocks on the network.

Quick View
See at a glance the current thermostat status throughout your building.

Copy Facility
Save time - copy comfort levels between rooms.

History
The TouchPad will store hours of temperature history.

USB Export
The temperature log can be exported via the USB connection.

Key Lock
Lock each thermostat to prevent misuse.

Product Dimensions (mm) & Wiring Specification

130
18
45
35

Note: Fits standrd 35mm depth back box

95

Wiring Detail

50

86

heatmiser